

IN THE CLAIMS

Please amend the claims as follows:

Claims 1-68 (Previously Canceled).

69. (Currently Amended) A method of remotely configuring communication apparatus for communication over a network to access a service, the method comprising ~~the steps of:~~
- connecting said communication apparatus to said network;
- automatically configuring said communication apparatus for communication using initial configuration data stored in said communication apparatus;
- said communication apparatus automatically communicating with a remote configuration system over said network using ~~the~~ stored initial configuration data;
- said communication apparatus transmitting unique identification information to said configuration system;
- at said configuration system determining configuration data for said communication apparatus dependent upon the unique identification information;
- transmitting said configuration data to said communication apparatus;
- storing said configuration data received from said configuration system ~~data in storage means~~ in said communication apparatus;
- controlling subsequent communications by said communication apparatus over said network using the stored configuration data;
- transmitting subsequent configuration data to said communication apparatus automatically from said configuration system;
- storing said subsequent configuration data in said ~~communication apparatus storage means~~; and
- controlling subsequent communications by said communication apparatus over said network in accordance with the stored subsequent configuration data.

70. (Previously Added) A method according to claim 69, including the steps of a user of said

Sub
Cl

communication apparatus generating a request for further subsequent configuration data, and transmitting said request to said configuration system to initiate the transmission of subsequent configuration data.

71. (Previously Added) A method according to claim 69, wherein said configuration data is transmitted over said network using a permanently open control channel associated with a plurality of data/voice channels.

Sub C1
72. (Previously Added) A method according to claim 69, including the steps at said communication apparatus, of:

gathering information on the use of said service;
processing said information to generate summary information; and
periodically transmitting said summary information to a provider of said service.

73. (Previously Added) A method according to claim 72, wherein said information is gathered in real time using a real time clock.

74. (Previously Added) A method according to claim 72, including the step of supplying said information and/or said summary information to a user.

75. (Currently Amended) Communication apparatus ~~for use in the method of claim 69~~ for interfacing a computer system to a communication network to access a service, the apparatus comprising:

first I/O ~~means~~ for connection to said computer system;
second I/O ~~means~~ for connection to the communication network;
a storage ~~means~~ for storing unique identification information and configuration data for configuring the operation of the apparatus to access said service over said communication network;

a processor - processing means for controlling said second I/O ~~means~~ the first time said second I/O ~~means~~ is connected to said communication network to connect to a remote

configuration system and to transmit said unique identification information in said storage ~~means~~ to the configuration system;

wherein said processor processing means is operable to control said second I/O ~~means~~ to initially receive configuration data from said configuration system, to store said initially received configuration data in said storage ~~means~~, and to control access to said service by said computer system in accordance with said initially received configuration data; and

wherein said processor processing means is operable to control said second I/O ~~means~~ to receive subsequent configuration data automatically generated by said configuration system, to store said subsequent configuration data in said storage ~~means~~, and to control subsequent access to said service by said computer system in accordance with said subsequent configuration data.

Sub C1
V
60

76. (Currently Amended) Communication apparatus according to claim 75, wherein said first I/O ~~means~~ comprises a local area network port for connection to a local area network.

77. (Currently Amended) Communication apparatus according to claim 75, wherein said second I/O ~~means~~ comprises an ISDN port for connection to one or more ISDN lines in said communications network.

78. (Currently Amended) Communication apparatus according to claim 77, wherein said second I/O ~~means~~ is adapted for connection to an ISDN line having a data channel (D) and a plurality of bearer channels (B).

79. (Previously Added) Communication apparatus according to claim 77, including at least one plain old telephone services (POTS) interface for connecting a telephone to the or each ISDN line.

80. (Currently Amended) Communication apparatus according to claim 75, including a user interface ~~means~~ for allowing a user to generate a request for further subsequent configuration data, said processor processing means being responsive to said request to control said second I/O ~~means~~ to transmit said request to said configuration system to cause further subsequent

configuration data to be transmitted to said apparatus.

81. (Currently Amended) Communication apparatus according to claim 75, wherein said second I/O ~~port means~~ comprises an ISDN interface for connection to one or more ISDN lines of an ISDN network having one or more channels permanently connecting said ISDN interface to the ISDN network, and for receiving said subsequent configuration data using said data channel.

82. (Previously Added) Communication apparatus according to claim 81, wherein said ISDN interface is adapted to receive said subsequent configuration data using one or more communication channels of the or each ISDN line.

Sub
C1 83. (Currently Amended) Communication apparatus according to claim 75, wherein said second I/O ~~means~~ is adapted for connection to a dedicated data communication line.

84. (Currently Amended) Communication apparatus according to claim 75, wherein said ~~processor processing means~~ is operable to gather information on the use of said service by said computer system, to process said information to generate summary information, and to control said second I/O ~~means~~ to periodically transmit said summary information to a provider of said service.

85. (Currently Amended) Communication apparatus according to claim 84, including real time clock ~~means~~, wherein said ~~processor processing means~~ is operable to use said real time clock ~~means~~ to gather real time information on the use of said service by said computer system.

86. (Currently Amended) Communication apparatus according to claim 84, including user interface ~~means~~ to allow a user of said communication apparatus access to said information.

87. (Currently Amended) Communication apparatus according to claim 86, wherein said user interface ~~means~~ comprises a further I/O means.

88. (Currently Amended) Communication apparatus according to claim 86, wherein said user interface ~~means~~ comprises a computer program running on said processor processing means to allow a user of said computer system access to said summary information via said first I/O ~~means~~.

89. (Currently Amended) Communication apparatus according to claim 88, wherein said user interface ~~means~~ comprises said processor processor means operating as a web server.

90. (Currently Amended) Communication apparatus according to claim 89, wherein said processor processing means is operable to gather and process said information using machine independent instructions for output to said user.

Sub C1
91. (Currently Amended) Communication apparatus according to claim 75, including an encoder encoding means for encoding said unique identification information before transmission by said second I/O ~~means~~.

92. (Currently Amended) Communication apparatus according to claim 75, including a decoder decoding means for decoding said initial and subsequent configuration data received in encoded form by said second I/O ~~means~~.

93. (Currently Amended) Communication apparatus according to claim 75, wherein said second I/O ~~means~~ includes a modem for connection to an analogue telephone line.

94. (Currently Amended) Communication apparatus ~~for use in the method of claim 69~~ for communicating with a remote system over a network to access a service, the apparatus comprising:

an I/O means for connection to the network;

a storage means for storing unique identification information and configuration data for the operation of the communication apparatus to access said service;

a processor processing means for controlling said I/O ~~means~~ in accordance with said

configuration data the first time said I/O ~~means~~ is connected to said network to connect to a remote configuration system and to transmit said unique identification information thereto;

wherein said processor processing means is operable to control said I/O ~~means~~ to initially receive configuration data from said configuration system, to store said initially received configuration data in said storage ~~means~~, and to control access to said service in accordance with said initially received configuration data; and

wherein said processor processing means is operable to control said I/O ~~means~~ to receive subsequent configuration data automatically generated by said configuration system, to store said subsequent configuration data in said storage ~~means~~, and to control subsequent access to said service in accordance with said subsequent configuration data.

Sub C1
V
95. (Currently Amended) Communication apparatus according to claim 94, including an interface means for allowing a user to generate a request for further subsequent configuration data, said processor processing means being responsive to said request to control said I/O ~~means~~ to transmit said request to said configuration system to cause further subsequent configuration data to be transmitted to said apparatus.

96. (Currently Amended) Communication apparatus according to claim 94, wherein said I/O ~~port means~~ comprises an ISDN interface for connection to one or more ISDN lines of an ISDN network having one or more data channels permanently connecting said ISDN interface to the ISDN network, and for receiving said subsequent configuration data using said data channel.

97. (Previously Added) Communication apparatus according to claim 96, wherein said ISDN interface is adapted to receive said subsequent configuration data using one or more communication channels of the or each ISDN line.

98. (Currently Amended) Communication apparatus according to claim 94, wherein said processor processing means is operable to gather information on the use of said service by said computer system, to process said information to generate summary information and to control said I/O ~~means~~ to periodically transmit said summary information to a provider of said service.

99. (Currently Amended) Communication apparatus according to claim 98, including real time clock ~~means~~, wherein said ~~processor processing means~~ is operable to use said real time clock ~~means~~ to gather real time information on the use of said service.

100. (Currently Amended) Communication apparatus according to claim 98, including user interface ~~means~~ to allow a user of said apparatus access to said information.

101. (Currently Amended) Communication apparatus Apparatus according to claim 100, wherein said user interface ~~means~~ comprises a computer program running on said ~~processor processing means~~ to allow access to said summary information.

Sub C1
102. (Currently Amended) Communication apparatus Apparatus according to claim 101, wherein said ~~processor processing means~~ is operable to gather and process said information using machine independent instructions for output to said user.

103. (Currently Amended) Communication apparatus Apparatus according to claim 94, including ~~an encoder encoding means~~ for encoding said unique identification information before transmission by said I/O ~~means~~.

104. (Currently Amended) Communication apparatus Apparatus according to claim 94, including ~~a decoder decoding means~~ for decoding configuring received in encoded form by said I/O ~~means~~.

105. (Currently Amended) A configuration system for use in the method of claim 69 and for connection to said communication apparatus according to claim 75 via a communication network, said configuration system comprising:

a third I/O ~~means~~ for connection to said communication network, and for receiving said unique identification information from said communication apparatus; and

a configuration processor ~~processing means~~ responsive to said unique identification

information to determine initial configuration data for said communication apparatus;

wherein said third I/O means is adapted to transmit said determined configuration data to said communication apparatus near said communications network; and

wherein said configuration processor processing means is operative to automatically determine updated configuration data and to cause said third I/O means to transmit said updated configuration data to said communication apparatus.

106. (Currently Amended) A configuration system according to claim 105, wherein said configuration processor processing means is operative to determine said configuration data using said unique identification information, information on the user or users of said communication apparatus, and information on the level of service required by the user or users.

Sub C1
V
107. (Previously Added) A configuration system according to claim 106, including obtaining means for obtaining said information on the user or users, and said information on the level of service required by the user or users.

108. (Currently Amended) A configuration system according to claim 107, wherein said obtaining means is adapted to obtain said information on the user or users, said information on the level of service required by the user or users, and expected unique identification information prior to receipt of said unique identification information by said third I/O means, and said configuration processor processing means is operative to determine said configuration data before receipt of said unique identification information using the information obtained by said obtaining means, to compare the received unique identification information with said expected unique identification, and to cause said third I/O means to transmit the configuration data if there is a match in the comparison.

109. (Previously Added) A configuration system according to claim 108, including means for storing a plurality of sets of said configuration data for a corresponding plurality of said expected unique identification information for a corresponding plurality of said communication apparatuses, wherein said configuration system can connect to a plurality of said communication

apparatuses.

110. (Currently Amended) A configuration system according to claim 105, wherein said configuration processor processing means is responsive to a request for configuration data received by said third I/O means from said communication apparatus to determine configuration data and control said third I/O means to transmit said determined configuration data.

111. (Currently Amended) A configuration system according to claim 105, including a decoder decoding means for decoding encoded unique identification information received from said apparatus.

112. (Currently Amended) A configuration system according to claim 109, including an encoder encoding means for encoding said configuration data for transmission to said apparatus.

Sub C1
113. (Currently Amended) Apparatus for interfacing a computer system to a communication line to access a service, the apparatus comprising:

a first I/O means for connection to said computer system;
a second I/O means for connection to said communication line;
a processor processing means for gathering information on the use made of said service by said computer system, for processing said information to generate processed information, and for controlling said second I/O means to transmit said processed information to a remote management system; and
a storage means for storing said information and/or said processed information.

114. (Currently Amended) Apparatus according to claim 113, including a clock means, said processor processing means being responsive to said clock means to gather said information with respect to time, to process said information periodically, and to cause said second I/O means to transmit said processed information periodically to said remote management system.

115. (Currently Amended) Apparatus according to claim 113, including a user interface means

to allow a user of said apparatus access to said information and/or said processed information in said storage ~~means~~.

116. (Currently Amended) Apparatus according to claim 115, wherein said user interface ~~means~~ comprises a further I/O ~~means~~.

117. (Currently Amended) Apparatus according to claim 115, wherein said user interface ~~means~~ comprises a computer program running on said processor processing means to allow a user of said computer system access to said information and/or said processed information via said first I/O ~~means~~.

118. (Currently Amended) Apparatus according to claim 117, wherein said user interface ~~means~~ comprises said processor ~~means~~ operating as a Web server.

119. (Currently Amended) Apparatus according to claim 118, wherein said processor processing means is operable to gather and process said information for output to said user using machine independent instructions.

120. (Currently Amended) Apparatus according to claim 113, wherein said second I/O ~~means~~ is adapted to receive configuration data from said management system, and said processor processing means is operative to process said information in accordance with said configuration data.

121. (Currently Amended) Apparatus for communicating with a remote system over a network to access a service, the apparatus comprising:

an I/O ~~means~~ for connection to the network;

a processor processing means for gathering information on the use made of said service by said apparatus, for processing said information to generate processed information, and for controlling said I/O ~~means~~ to transmit said processed information to a remote management system; and

Sub
C)

a storage means for storing said information and/or said processed information.

122. (Currently Amended) Apparatus according to claim 121, including a clock means, said processor processing means being responsive to said clock means to gather said information with respect to time, to process said information periodically, and to cause said I/O means to transmit said processed information periodically to said remote management system.

123. (Currently Amended) Apparatus according to claim 121, including a user interface means to allow a user of said apparatus access to said information and/or said processed information in said storage means.

124. (Currently Amended) Apparatus according to claim 123, wherein said user interface means comprises a computer program running on said processor processing means to allow a user access to said information and/or said processed information.

125. (Currently Amended) Apparatus according to claim 124, wherein said processor processing means is operable to gather and process said information for output to said user using machine independent instructions.

126. (Currently Amended) Apparatus according to claim 123, wherein said I/O means is adapted to receive configuration data from said management system, and said processor processing means is operative to process said information in accordance with said configuration data.

127. (Previously Added) A method of monitoring communications between a communication apparatus and a remote system over a network to access a service, the method comprising the steps at said communication apparatus, of:

gathering information on the use of said service by said communication apparatus;
processing said information to generate processed information; and
transmitting said processed information to a remote management system.

✓
Sub
C1

128. (Previously Added) A method according to claim 127, wherein said information is gathered with respect to time, processed periodically, and periodically transmitted to said remote management system.

129. (Previously Added) A method according to claim 127, including the step of supplying said information and/or said processed information to a user.

130. (Previously Added) Communication apparatus for the performance of communication process over a network comprising:

means for transmitting, in accordance with a first configuration condition of said communication apparatus, unique identification information over said network from said communication apparatus to a remote configuration system for obtaining first reconfiguration data from said remote configuration system;

means for receiving said first reconfiguration data from said remote configuration system and storing said received first reconfiguration data in said communication apparatus;

means for re-configuring said communication apparatus in accordance with said stored first reconfiguration data to place said communication apparatus in a first reconfiguration condition to permit said communication apparatus to perform communication processes over said network in accordance with said first reconfiguration condition; and

means operable on command received from said network for:

receiving second reconfiguration data via said network;

storing said second reconfiguration data in said communication apparatus; and

further reconfiguring said communication apparatus in accordance with said second reconfiguration data to place said communication apparatus in a second reconfiguration condition to permit said communication apparatus to perform communication processes over said network in accordance with said second reconfiguration condition.

131. (Previously Added) Communication apparatus for the performance of communication processes over a network, comprising:

means for transmitting, in accordance with a first configuration condition of said communication apparatus, unique identification information over said network from said communication apparatus to a remote configuration system for obtaining first reconfiguration data from said remote configuration system;

means for receiving said first reconfiguration data from said remote configuration system and storing said received first reconfiguration data in said communication apparatus;

means for re-configuring said communication apparatus in accordance with said stored first reconfiguration data to place said communication apparatus in a first reconfiguration condition to permit said communication apparatus to perform communication processes over said network in accordance with said first reconfiguration condition;

means for receiving second reconfiguration data via said network and storing said second reconfiguration data in said communication apparatus, upon command received from said network; and

means for further re-configuring said communication apparatus in accordance with said second reconfiguration data to place said communication apparatus in a second reconfiguration condition to permit said communication apparatus to perform communication processes over said network in accordance with said second reconfiguration condition.

132. (Previously Added) Server apparatus for communication via a network with a plurality of reconfigurable communication devices, comprising:

means for storing a plurality of different first reconfiguration data relating to different said communication devices;

means responsive to receipt of unique identification data from a said communication device for transmitting to said communication device via said network said first reconfiguration data relating thereto for permitting said communication device to be placed in a first reconfiguration condition defined by said first reconfiguration data; and

means for transmitting to said communication device via said network second reconfiguration data for causing said communication devices to be further reconfigured into second reconfiguration conditions in accordance with said second reconfiguration data, on command of said server apparatus.

Sub
C1

133. (Previously Added) A process for configuring a communication apparatus for the performance of communication processes over a network, comprising:

transmitting, in accordance with a first configuration condition of said communication apparatus, unique identification information over said network from said communication apparatus to a remote configuration system for obtaining first reconfiguration data from said remote configuration system;

receiving said first reconfiguration data from said remote configuration system and storing said received first reconfiguration data in said communication apparatus;

re-configuring said communication apparatus in accordance with said stored first reconfiguration data to place said communication apparatus in a first reconfiguration condition to permit said communication apparatus to perform communication processes over said network in accordance with said first reconfiguration condition; and

upon command received from said network:

receiving second reconfiguration data via said network;

storing said second reconfiguration data in said communication apparatus, and

further re-configuring said communication apparatus in accordance with said second reconfiguration data to place said communication apparatus in a second reconfiguration condition to permit said communication apparatus to perform communication processes over said network in accordance with said second reconfiguration condition.

134. (Previously Added) A process for configuring a communication apparatus for the performance of communication processes over a network, comprising:

transmitting, in accordance with a first configuration condition of said communication apparatus, unique identification information over said network from said communication apparatus to a remote configuration system for obtaining first reconfiguration data from said remote configuration system;

receiving said first reconfiguration data from said remote configuration system and storing said received first reconfiguration data in said communication apparatus;

re-configuring said communication apparatus in accordance with said stored first

Sub
C1

reconfiguration data to place said communication apparatus in a first reconfiguration condition to permit said communication apparatus to perform communication processes over said network in accordance with said first reconfiguration condition;

receiving second reconfiguration data via said network and storing said second reconfiguration data in said communication apparatus, upon command received from said network; and

further re-configuring said communication apparatus in accordance with said second configuration data to place said communication apparatus in a second reconfiguration condition to permit said communication apparatus to perform communication processes over said network in accordance with said second reconfiguration condition.

135. (Currently Amended) A process for enabling reconfiguration of a plurality of reconfigurable communication devices operable for performing communication operations over a network, comprising:

storing at server means a plurality of different first reconfiguration data relating to different said communication devices;

in response to receipt by the server means of unique identification data from a said communication device transmitting to said communication device via said network said first reconfiguration data relating thereto for permitting said communication device to be placed in a first reconfiguration condition defined by said first reconfiguration data; and

on command of the server means, transmitting to said communication devices via said network second reconfiguration data for causing said communication devices to be further reconfigured into second reconfiguration conditions in accordance with said second reconfiguration data.